



Marine Grease

Biobased Lubricating Grease

Part No: 10325, 10326

DESCRIPTION

UltraLube® Marine Grease is a premium quality biobased, biodegradable, water resistant grease formulated from USA-grown vegetable oils and a lithium complex-based thickener and extreme pressure additives for maximum performance.

APPLICATIONS

- ▶ Ideal for wheel bearings, trailer bearings, gimble bearings, prop shafts, cables, swivel hinges, pins, winches and anchor chain reels
- ▶ Recommended for marine applications
- ▶ Excellent for extreme pressure applications
- ▶ Prevents rust and corrosion
- ▶ Designed for protection between all metal to metal contact areas
- ▶ Recommended for environmentally sensitive areas near waterways
- ▶ Replaces and mixes freely with petroleum based grease

BENEFITS

- ▶ Excellent oxidative and high-temperature stability
- ▶ Contains extreme pressure additives to minimize friction and wear
- ▶ Superior lubricity reduces heat and lessens energy consumption
- ▶ Higher flash point than petroleum based greases for increased safety
- ▶ Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- ▶ USDA BioPreferred™ listed and approved
- ▶ Manufactured from renewable USA-grown crop based oils

PERFORMANCE LEVELS

- ▶ Meets NLGI "GC-LB" classification for wheel bearing and chassis lubricant
- ▶ Operating temperature range -40°F (-40°C) to +427°F (+219°C)

TYPICAL PROPERTIES

Property	Method	Value
Appearance	visual	Red
NLGI Grade	2	
Cone Penetration, worked 60X	ASTM D-217	260-290
Four Ball Wear Scar (mm)	ASTM D-2266	0.47
Four Ball Weld Load (kg)	ASTM D-2596	500
Four Ball Load Wear Index (kg)	ASTM D-2596	60
Timken OK Load (lbs.)	ASTM D-2509	40
Drop Point °C (°F)	ASTM D-2265	275 (527)
Oil Separation	ASTM D-1742	<3%
Water Resistance @80°C (% loss)	ASTM D-1264	11.6%
Base Oil Viscosity at 40°C (cSt)	ASTM D-445	86
Base Oil Viscosity at 100°C (cSt)	ASTM D-445	16
Base Oil Viscosity Index	ASTM D-2270	202
Base Oil Flash Point °C (°F)	ASTM D-92	326 (619)
Base Oil Biodegradability	OECD	Pass
Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

PACKAGING

3-oz cartridge

14-oz cartridge

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.