



# Hi-Visc Rail Curve Grease w/MoS<sub>2</sub>

## Biobased Rail Curve Lubricant

Part No: 10960, 10961

### DESCRIPTION

UltraLube Hi-Visc RCG w/molybdenum disulphide is a premium quality biobased, biodegradable rail curve lubricant formulated from USA-grown vegetable oils and a lithium-based thickener.

### APPLICATIONS

- ▶ Designed for wayside applicators with wide temperature requirements
- ▶ For use in mechanical or electric gauge face lubricators
- ▶ Pumps and carries when using wayside application equipment and grease temperature is between 2°C (35°F) and 71°C (160°F)
- ▶ Recommended for heavy load applications such as coal trains
- ▶ Recommended for environmentally sensitive areas near waterways

### BENEFITS

- ▶ Contains advanced extreme pressure additives and molybdenum disulphide to enhance the effects for unsurpassed protection from wear
- ▶ Reduces friction and wear between track and wheel flange
- ▶ Formulated to resist port plugging in wiping bars
- ▶ Longer carry down track from lubricator
- ▶ Better gauge face coefficient of friction than most petroleum-based grease
- ▶ Less migration to top of rail than major petroleum-based grease
- ▶ Improves fuel efficiency and superior lubricity
- ▶ Higher flash point than petroleum greases for increased safety
- ▶ Biodegradable formula reduces damage to the environment
- ▶ Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- ▶ Meets USDA's proposed Biobased product definition for EO13101
- ▶ Manufactured from renewable USA-grown crop based oils

### PERFORMANCE LEVELS

- ▶ Recommended for all Portec® and other brand lubricators

### TYPICAL PROPERTIES

Property	Method	Value
Appearance	visual	Dark Gray to Black
Cone Penetration, unworked	ASTM D-217	310
Four Ball Wear Scar (mm)	ASTM D-2266	0.4
Four Ball Weld Load (kg)	ASTM D-2596	500
Drop Point °C (°F)	ASTM D-2265	199 (390)
Base Oil Viscosity at 40°C (cSt)	ASTM D-445	86
Base Oil Viscosity at 100°C (cSt)	ASTM D-445	16
Base Oil Viscosity Index	ASTM D-2270	201
Base Oil Flash Point °C (°F)	ASTM D-92	326 (619)
Base Oil Biodegradability	OECD	Pass
Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

### PACKAGING

35-lb Pail, 400-lb Drum, Totes

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.