



Lo-Visc Rail Curve Grease w/MoS₂ Biobased Rail Curve Lubricant

Part No: 10965, 10966

DESCRIPTION

UltraLube Lo-Visc RCG w/MoS₂ is a premium quality biobased, biodegradable rail curve lubricant formulated from USA-grown vegetable oils and a lithium-based thickener.

APPLICATIONS

- ▶ Designed for wayside applicators with wide temperature requirements
- ▶ Ideal for prolonged cold temperatures
- ▶ Suitable for Hi-Rail applications
- ▶ Pumps and carries when using wayside application equipment and grease temperature is between -18°C (0°F) and 38°C (100°F)
- ▶ Recommended for heavy load applications such as coal trains
- ▶ Recommended for environmentally sensitive areas near waterways

BENEFITS

- ▶ Contains advanced extreme pressure additives and molybdenum disulphide to enhance the effects for unsurpassed protection from wear
- ▶ Reduces friction and wear between track and wheel flange
- ▶ Formulated to resist port plugging in wiping bars
- ▶ Longer carry down and increased retention
- ▶ Better gauge face coefficient of friction than most petroleum-based grease
- ▶ Less migration to top of rail than major petroleum-based grease
- ▶ Improves fuel efficiency and superior lubricity
- ▶ Higher flash point than petroleum greases for increased safety
- ▶ Biodegradable formula reduces damage to the environment
- ▶ Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- ▶ Meets USDA's proposed Biobased product definition for EO13101
- ▶ Manufactured from renewable USA-grown crop based oils

PERFORMANCE LEVELS

- ▶ Recommended for all Portec® and other brand lubricators

TYPICAL PROPERTIES

Property	Method	Value
Appearance	visual	Dark Gray to Black
Cone Penetration, unworked	ASTM D-217	310-340
Four Ball Wear Scar (mm)	ASTM D-2266	0.4
Four Ball Weld Load (kg)	ASTM D-2596	500
Drop Point °C (°F)	ASTM D-2265	191 (376)
Base Oil Viscosity at 40°C (cSt)	ASTM D-445	86
Base Oil Viscosity at 100°C (cSt)	ASTM D-445	16
Base Oil Viscosity Index	ASTM D-2270	201
Base Oil Flash Point °C (°F)	ASTM D-92	326 (619)
Base Oil Biodegradability	OECD	Pass
Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

PACKAGING

35-lb Pail, 400-lb Drum, Totes

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.