



UltraLube® Cutting Oil

Biobased Cutting Oil

Part No: 10650, 10651, 10652

DESCRIPTION

UltraLube Cutting Oil is a high performance cutting and way fluid. Formulated with the best optimized natural seed oils and select additives, it surpasses the lubricity and performance of conventional metalworking fluids.

APPLICATIONS

- ▶ General purpose cutting and grinding fluid
- ▶ Milling, tapping and reaming
- ▶ Gear cutting, broaching and screw machining
- ▶ Gun drilling

BENEFITS

- ▶ Improves surface finishes in machining and grinding operations
- ▶ Superior lubricity maximizes feed rates and improves productivity
- ▶ Reduces chip welding so tools remain free cutting
- ▶ Cooler operating and less smoke allow higher operating speeds
- ▶ Less mist generation
- ▶ Safe for all metals
- ▶ Non-staining
- ▶ Improves centricity, accuracy and part run-out
- ▶ Improves part quality by reducing tool or wheel pressure
- ▶ Helps your business comply with ISO-14000
- ▶ Does not contain chlorine
- ▶ High flash and fire points
- ▶ Because of its multiple uses, UltraLube can reduce product inventory

TYPICAL PROPERTIES

Property	Method	Value
Appearance	Visual	Light Yellow
Base Oil Viscosity at 40°C (cSt)	ASTM D-445	40
Base Oil Viscosity at 100°C (cSt)	ASTM D-445	8.5
Flash Point °C (°F)	ASTM D-92	310 (590)
Pour Point °C (°F)	ASTM D-97	-20 (-4)
Four Ball Wear Scar (mm)	ASTM D-4172	0.30
Pin & Vee Block Test (lbs)	ASTM D-3233A	>3,335
Non-Staining	ASTM D-130-56	1B
Base Oil Biodegradability	OECD	Pass
Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

PACKAGING

1-gallon 5-gallon 55-gallon

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.