



Semi-Synthetic Metal Working Coolant

Biobased Coolant

Part No: 10660, 10661, 10662

DESCRIPTION

UltraLube Coolant is based on a new technology that provides superior lubrication and cooling. The product is specially formulated with extra lubricity to perform well on a wide range of metals including aluminum and stainless steel. UltraLube Coolant is very safe for workers and the environment. It is made with renewable, environmentally friendly plant based esters.

APPLICATIONS

- ▶ All types of machines
- ▶ High pressure pumps
- ▶ All metals including aluminum alloys and stainless steel
- ▶ individual or central sumps

BENEFITS

- ▶ Economical – reduced drag out consumption and decreased consumption from evaporation
- ▶ Universal product designed to be used for machining the widest range of metals
- ▶ Very high resistance to micro-organisms
- ▶ Virtually odorless
- ▶ High dispersion, increases cleanliness of machines
- ▶ Simple degreasing with alkaline cleaner or solvent
- ▶ No foaming in soft or hard water or from high pressure
- ▶ Corrosion: Steel 0-0, Copper 0-0, Aluminum 0-0
- ▶ Contains no phenolics, nitrites, glycol ethers, DEA, formaldehyde or silicone

USAGE RECOMMENDATIONS

Refractometer Factor	1.8
To compute actual concentration – multiply reading taken by the Refractometer factor	
Normal Refractometer Reading	4
Normal Operating Ph	9.3
Keep from freezing	
Recommended Max Storage	6 months, under original packaging
Concentration Ranges	
- Grinding	30:1 to 20:1 (3% to 5%)
- Machining w/Carbide Tools	20:1 to 17:1 (5% to 6%)
- Machining w/High-Speed Steel	
- Tools	15:1 to 12:1 (6% to 8%)

PACKAGING

1-gallon

5-gallon

55-gallon

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.