



UltraLube® Slide Way Oil ISO46

Biobased Slide Way Lubricant

Part No: 10681, 10682

DESCRIPTION

UltraLube Biobased ISO46 Slide Way Oil is a premium, biodegradable slide way lubricant formulated for lubricating machine tool ways, slides and guides. Formulated with the best-optimized vegetable seed oils and select friction reducing additives to provide excellent lubricity and extreme pressure properties.

APPLICATIONS

- ▶ Recommended for ways and slides and other sliding surfaces of machine tools such as grinders, milling machines, planers and saw guides
- ▶ For use on all flat or V-shaped surfaces
- ▶ Recommended for both vertical and horizontal ways
- ▶ Recommended for use with UltraLube Semi-Synthetic Metal Working Coolant to reduce tramp oil contamination

BENEFITS

- ▶ Bio-stable formulation
- ▶ Exceptional load carrying and anti-wear properties protect ways and guides
- ▶ Low stick-slip properties provide smooth operation and accurate work even at slow speeds (Passed Cincinnati Milacron Slip-Stick Test)
- ▶ Good adhesion improves non-drip characteristics and reduces run-off and dripping in vertical ways and reduces oil loss
- ▶ Good bacteria and fungal protection
- ▶ Works synergistically with bio-based water soluble lubricants
- ▶ Does not contain toxic chlorine or sulfur
- ▶ Reduces tramp oil from ways when used together with UltraLube Coolant
- ▶ Higher flash point than petroleum-based way lubricants – safer to store & operate
- ▶ Biodegradable formulation

TYPICAL PROPERTIES

Property	Method	Value
Appearance	Visual	Amber
ISO Viscosity Grade		46
Flash Point °C (°F)	ASTM D-92	291 (556)
Base Oil Biodegradability	OECD	Pass

PACKAGING

5-gallon 55-gallon

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.