

# ALWAYS IN GOOD FORM.

Specifically formulated for use with concrete and asphalt, UltraLube® outperforms and outlasts traditional petroleum-based products while also offering a non-toxic formula that's safer for your workers and your customers.

UltraLube concrete and asphalt form release is a water-soluble, biodegradable, non-toxic, stain-free form release agent with biobased seed oil that permits easy removal of wood or steel forms.

**4X** MORE LUBRICATION

## SUPERIOR PERFORMANCE

- UltraLube base oils have **4x\*** the lubricity of petroleum base oils
- Naturally higher viscosity, which reduces friction, heat and wear – especially in high-speed applications
- Last longer than petroleum-based lubricants and are less likely to “thin down” at higher temperatures
- Higher flash and fire points than petroleum-based products
- Mix readily with conventional petroleum-based products

## GETS IN, STAYS ON™

Powerful, professional-grade UltraLube instantly penetrates, creating long-lasting bonds to metal.

- Vegetable-based oil molecules are “polar;” they bond and adhere to metal. Petroleum-based oil molecules aren’t; they simply run off.

**eco safe**

## ECO-SAFE AND NON-TOXIC

UltraLube lubricants are professional-grade, eco-safe, non-toxic products manufactured from a renewable resource – biodegradable vegetable base stock oil – and made in the USA.

- Biodegradable
- Base oil is derived from vegetables – a renewable resource
- Contain no zinc or chlorine
- No harsh odors
- Neutral in water
- Are safer for your workers and the environment



\* Test (ASTM D3233) conducted by the National Ag-Based Lubricants Center (NABL) using UltraLube® high oleic base oil and three different viscosities of petroleum base oils. Compare the UltraLube® base oil result of 1,756 lbF (pounds of force) to the average of petroleum base oils of 434 lbF – UltraLube® has four times the lubricity, or friction-reducing capability, of petroleum-based oil.



DON'T  
DO WEAK



**UltraLUBE®**

## Concrete and Asphalt Form Release

### Concrete/Asphalt Form Release

- Water soluble
  - Biodegradable and virtually non-toxic
  - Applies easily with sprayer, brush or roller
  - Non-staining to concrete
  - No unpleasant smell, toxic fumes or diesel odor
  - Promotes clean and easy removal of wood or steel forms
  - Less flammable than petroleum-based agent
  - Meets federal and California VOC regulations
  - Promotes longer form life
  - Manufactured from renewable resources
  - Use 10% to 20% solution with water for concrete and 5% to 10% solution for asphalt
  - Viscosity 48
  - High Flash Point 550°F (288°C)
- 10900** 5 gallon (18.9 l) plastic pail with pour spout.  
**10901** 55 gallon (208.1 l) drum.



10900



10901

