

HANDLES THE PRESSURE.

- Biobased, biodegradable, non-toxic formulations
- Superior lubricity reduces operating temperatures
- Extends component life

4x
MORE
LUBRICATION





**DON'T
DO WEAK** **USE**

UltraLUBE®

Tractor Hydraulic Fluid and Hydraulic Oils

Specifically formulated for hydraulic machinery, UltraLube® hydraulic oils surpass the lubricity and performance of conventional lubrication products.

UltraLube's hydraulic oils help stop rust and corrosion, reduce friction between moving parts and are safe for metal-to-metal applications. They provide excellent corrosion protection under severe conditions, reduce heat and wear better than petroleum-based fluids, and have higher flash points for improved safety. UltraLube hydraulic oils are chlorine free.

4x MORE LUBRICATION

SUPERIOR PERFORMANCE

- UltraLube base oils have **4x*** the lubricity of petroleum base oils
- Naturally higher viscosity, which reduces friction, heat and wear – especially in high-speed applications
- Last longer than petroleum-based lubricants and are less likely to “thin down” at higher temperatures
- Higher flash and fire points than petroleum-based products
- Mix readily with conventional petroleum-based products

GETS IN, STAYS ON™

Powerful, professional-grade UltraLube instantly penetrates, creating long-lasting bonds to metal.

- Vegetable-based oil molecules are “polar;” they bond and adhere to metal. Petroleum-based oil molecules aren't; they simply run off.

eco safe

ECO-SAFE AND NON-TOXIC

UltraLube lubricants are professional-grade, eco-safe, non-toxic products manufactured from a renewable resource – biodegradable vegetable base stock oil – and made in the USA.

- Biodegradable
- Base oil is derived from vegetables – a renewable resource
- Contain no zinc or chlorine
- No harsh odors
- Neutral in water
- Are safer for your workers and the environment

* Test (ASTM D3233) conducted by the National Ag-Based Lubricants Center (NABL) using UltraLube® high oleic base oil and three different viscosities of petroleum base oils. Compare the UltraLube® base oil result of 1,756 lbF (pounds of force) to the average of petroleum base oils of 434 lbF – UltraLube® has four times the lubricity, or friction-reducing capability, of petroleum-based oil.



Universal Hydraulic Tractor Fluid

- Designed for equipment using a shared hydraulic fluid reservoir operating clutches, brakes and lift systems
- Protects against wear, brake chatter and clutch slippage
- Superior lubricity protects pumps, valve cylinders and other hydraulic components
- Prevents corrosion of non-ferrous metal parts
- Meets or exceeds John Deere® Wear/Corrosion Test, Piston Pump AT 94661 and Flow Degradation Tests, and Vickers 35-VQ Vane Pump Test
- ASTM D-130 Copper Corrosion is 1A
- USDA BioPreferred oil
- Viscosity Index 230
- Pour Point -13°F (-25°C)
- Flash Point 426°F (219°C)

10571 5 gallon (18.9 l) plastic pail with pour spout.

John Deere is a registered trademark of Deere & Company.



10571

Hydraulic Oil ISO32/46/68

- Maintains stable viscosity through wide temperature ranges
- Reduces wear through superior thin-film protection
- Particularly suited for use near water, in forestry, agriculture, golf courses, etc.

Part No.	ISO Grade	Viscosity	🔥 Pour Point	🔥 Flash Point
10557 (not shown)	32	214	-33°F (-36°C)	406°F (208°C)
10560	46	223	-13°F (-25°C)	493°F (256°C)
10563 (not shown)	68	196	-11°F (-24°C)	500°F (260°C)

Passes Vickers 20-VQ, 35-VQ and 104C Vane Pump Tests. Rust and corrosion protection to ASTM D-130 is 1A. Shipped in 5 gallon (18.9 l) plastic pails with pour spouts.



10560

Hydraulic Jack Oil ISO22

- Recommended for industrial and home floor and bottle hydraulic jacks
- Reduces wear through superior thin film protection
- Protects all ferrous metal components from rust and corrosion
- Superior performance for brass and bronze-on-steel contacts
- Maintains stable viscosity through a wide operating temperature range
- Pour Point 0°F (-18°C)
- Flash Point 322°F (161°C)

10573 1 quart (.946 l) with “yorker” cap for easy filling. 12 per carton.

10574 1 gallon (3.78 l) bottle. 4 per carton.

10575 5 gallon (18.9 l) plastic pail with pour spout.



10573



10574



10575

Elevator Hydraulic Oil ISO46

- Specifically engineered for elevator hydraulic systems
- Reduces wear through superior thin film protection and protects all ferrous metal components from rust and corrosion
- Maintains stable viscosity through a wide operating temperature range
- Recommended for systems with underground hydraulic lines where leaks are hard to find
- Recommended for Green Building Council, LEEDS projects
- Pour Point -27°F (-33°C)
- Flash Point 594°F (312°C)

10800 5 gallon (18.9 l) plastic pail with pour spout.



10800

Hydraulic Oil ISO220

- Maintains stable viscosity through wide temperature ranges
- Reduces wear through superior thin-film protection
- Particularly suited for use near water, in forestry, agriculture, golf courses, etc.
- Pour Point -4°F (-20°C)
- Flash Point 529°F (276°C)

10594 (not shown) 5 gallon (18.9 l) plastic pail with pour spout.

10595 55 gallon (208.1 l) drum.

Passes Vickers 20-VQ, 35-VQ and 104C Vane Pump Tests. Rust and corrosion protection to ASTM D-130 is 1A.



10595



Visit us online at UltraLube.com

UltraLube professional-grade lubricants are available at retail stores across North America. Our products are also available for wholesale purchase for business purposes through national and local industrial suppliers and automotive distributors. **Visit UltraLube.com to find out where to buy.**

Download a catalog online

Visit our online resource center to download the UltraLube product catalog. www.UltraLube.com/ProductCatalog



Plews & Edelmann
1550 Franklin Grove Road, Dixon, IL 61021 USA
Telephone: 800-770-4639, Fax: 815-288-3388
www.UltraLube.com | www.facebook.com/UltraLube
© 2012 Plews & Edelmann | Printed in USA