



MEET YOUR TOUGHEST CREW MEMBER

- Biobased, biodegradable, non-toxic formulations
- Superior lubricity reduces operating temperatures
- Extends component life

Specifically formulated for usage in harsh, marine conditions, UltraLube® heavy-duty products surpass the lubricity and performance of conventional lubrication products.

UltraLube's rugged marine lubricants help stop rust and corrosion, reduce friction between moving parts and are safe for metal-to-metal applications. They provide excellent corrosion protection under severe conditions, reduce heat commonly found with petroleum-based fluids, and have higher flash points for improved safety. UltraLube marine lubricants are chlorine free.

SUPERIOR PERFORMANCE

- UltraLube base oils have **4x*** the lubricity of petroleum base oils
- Naturally higher viscosity, which reduces friction, heat and wear – especially in high-speed applications
- Last longer than petroleum-based lubricants and are less likely to “thin down” at higher temperatures
- Higher flash and fire points than petroleum-based products
- Mix readily with conventional petroleum-based products

GETS IN, STAYS ON™

Powerful, professional-grade UltraLube instantly penetrates, creating long-lasting bonds to metal.

- Vegetable-based oil molecules are “polar;” they bond and adhere to metal. Petroleum-based oil molecules aren't; they simply run off.

4x MORE LUBRICATION

ecosafe

ECO-SAFE AND NON-TOXIC

UltraLube lubricants are professional-grade, eco-safe, non-toxic products manufactured from a renewable resource – biodegradable vegetable base stock oil – and made in the USA.

- Biodegradable
- Base oil is derived from vegetables – a renewable resource
- Contain no zinc or chlorine
- No harsh odors
- Neutral in water
- Are safer for your workers and the environment



* Test (ASTM D3233) conducted by the National Ag-Based Lubricants Center (NABL) using UltraLube® high oleic base oil and three different viscosities of petroleum base oils. Compare the UltraLube® base oil result of 1,756 lbF (pounds of force) to the average of petroleum base oils of 434 lbF – UltraLube® has four times the lubricity, or friction-reducing capability, of petroleum-based oil.



DON'T DO WEAK USE

UltraLUBE®

Marine Lubricants

Marine & Trailer Bearing Grease

- Special water washout-resistant formulation ideal for marine applications
- Meets NLGI's tough GC-LB specifications
- Provides excellent corrosion protection under severe conditions
- For use on wheel bearings (including disc brake applications), swivel hinges, pins, winches, anchor chain reels, steering cables, gimbal bearings and other marine parts that require greasing

- NLGI Grade 2, "GC-LB" Rating
- Drop Point 527°F (275°C)
- Flash Point 619°F (326°C)

- 10325** 3 oz. (85 grams) cartridge. 3 cartridges per bag. Total 9 oz. (255 grams). 10 bags per case-cut carton.
- 10326** 14 oz. (397 grams) cartridge. 10 per case-cut carton.

Operating Temperature Range
-40°F (-40°C) to +427°F (+219°C)
Base Type – Lithium Complex, Color – Blue



10325

10326

Marine High Viscosity Lower Unit Gear Lube SAE 80w/90

- Biobased, biodegradable high-performance lower unit gear oil
- Designed for high-performance, high load and high torque applications in today's high horsepower outboards and stern drives
- Designed to meet API GL-5 requirements
- Superior lubricity protects gears from wear and reduces vibration and noise

- USDA BioPreferred oil
- Pour Point -17°F (-27°C)
- Flash Point 468°F (242°C)

- 10600** 1 quart (.946 l) with "yorker" cap for easy filling. 12 per carton.
- 10601** 5 gallon (18.9 l) plastic pail with pour spout.



10600

10601

Marine Power Trim & Tilt Fluid

- Biobased, biodegradable high-performance power trim and tilt fluid
- Formulated to provide superior lubricity to ensure proper pump performance, long seal life and quiet, smooth operation
- Combats high operating pressures and resists rust, oxidation and foaming

- Extreme pressure additives ensure excellent stability and shear resistance
- Pour Point -33°F (-36°C)
- Flash Point 406°F (208°C)

- 10603** 10 fl. oz squeeze tube (280 ml). 6 per case-cut carton.



10603

